


MATERIAL STANDARD

SPLICE, COPPER COMPRESSION



- Copper Compression Splices** are intended primarily for connecting underground cables. The splices shall meet the physical dimensions and tool-die requirements listed below.
- Stock Unit:** EA

Wire Size	L, in.	OD, in.	Tool - Die			Wire Size	L, in.	OD, in.	Tool - Die		
			Burndy	Kearney	T&B				Burndy	Kearney	T&B
#6	1-3/4	0.29	7	-	24	4/0	3-3/8	0.69	15	5/8	54
#4	1-3/4	0.34	8	5/16	29	250	3-3/8	0.75	16	11/16	60
#2	1-7/8	0.42	10	3/8	33	300	4-1/8	0.81	17	7/8	66
#1	1-7/8	0.46	11	3/8	37	350	4-1/8	0.88	18	8/8	71
1/0	2-7/8	0.51	12	1/2	42	500	4-5/8	1.06	20	1	87
2/0	3-1/8	0.56	13	9/16	45	750	5-7/8	1.30	24	1-5/16	106
3/0	3-1/8	0.62	14	5/8	49-50	1000	6	-	27	-	125

3. Approved Manufacturers

Stock Number	Wire AWG /kcmil	Anderson	Burndy	Dossert	Homac	Mac	Penn-Union	Richards	ILSCO/ Utilco
677354	6	VHSS-6	YS6C-L	DPCS 2	SC-6	MSC 6	BCU-6	SCC3	CT-6
677355	4	VHSS-4	YS4C-L	DPCS 4	SC-4	MSC 4	BCU-4	SCC5	CT-4
677357	2	VHSS-2	YS2C-L	DPCS 6	SC-2	MSC 2	BCU-2	SCC7	CT-2
677358	1	VHSS-1	YS1C-L	DPCS 8	SC-1	MSC 1	BCU-1	SCC8	CT-1
677359	1/0	VHS-1/0	YS25	DPC 10	C-1/0	MRC 1/0	BBCU-1/0	CC9	CTL-1/0
677360	2/0	VHS-2/0	YS26	DPC 13	C-2/0	MRC 2/0	BBCU-2/0	CC10	CTL-2/0
677361	3/0	VHS-3/0	YS27	DPC 17	C-3/0	MRC 3/0	BBCU-3/0	CC11	CTL-3/0
677362	4/0	VHS-4/0	YS28	DPC 21	C-4/0	MRC 4/0	BBCU-4/0	CC12	CTL-4/0
677363	250	VHS-250	YS29	DPC 25	C-250	MRC 250	BBCU-025	CC13	CTL-250
677364	300	VHS-300	YS30	DPC 30	C-300	MRC 300	BBCU-030	CC14	CTL-300
677365	350	VHS-350	YS31	DPC 35	C-350	MRC 350	BBCU-035	CC15	CTL-350
677367	500	VHS-500	YS34	DPC 50	C-500	MRC 500	BBCU-050	CC18	CTL-500
677371	750	VHS-750	YS39	DPC 75	C-750	MRC 750	BBCU-075	CC23	CTL-750
677373	1000	VHS-1000	-	DPC 100	C-1000	-	BBCU-100	-	-

STANDARDS COORDINATOR

John Shipek
 John Shipek

STANDARDS SUPERVISOR

John Barnett
 John Barnett

UNIT DIRECTOR

Richard Kent
 Richard Kent