
STANDARD NUMBER:__

1 of 1 PAGE OF PAGES

DATE: Sept. 2, 1959

MATERIAL STANDARD PORCELAIN ENAMEL NAMEPLATES

REV: June 29, 1990



GENERAL: Porcelain enamel namplates shall be manufactured in accordance with Porcelain Enamel Institute Standard PEI: S-100, latest revision.

PLATES: 20 gauge enameling grade sheet iron shall be of the dimensions shown in the details above and as indicated in the purchase order. Each plate shall have four holes 3/8" in diameter located as shown in the typical mounting hole arrangement above. The holes shall be drilled or punched before enameling. The four corners of the plates shall be rounded off to 1/2" radius.

GROMMETS: After enameling, each hole in the plates shall be equipped with a vinyl grommet, Walsco Cat. 7034, or equal, with 1/4" I.D. for 3/8" mounting hole.

LETTERING: Letters and numerals shall be U.S. Bureau of Public Roads Standards, Series "C" and size shown above and as indicated in the purchase order. All lettering, except that of Detail "D" and "F" shall be black on a yellow background. Lettering of Detail "D" and "F" shall be white on a red background.

COLORS: Colors shall be in accordance with Porcelain Enamel Institute color standard PEI: CG-1 and designated: yellow PEI-7, red PEI-12; black PEI-28; white PEI-1.

ORIGINATOR STANDARDS SUPERVISOR STANDARDS COORDINATOR UNIT DIRECTOR In Shome