

## Duct Tape, Cloth, Waterproof



### 1. Scope

This standard covers the requirements for waterproof cloth duct tape.

This standard applies to Seattle City Light (SCL) Stock No. 736745.

### 2. Application

Duct tape is used to seal polychlorinated biphenyl (PCB) and asbestos suits and plastic sheets. Suitable for use on rough surfaces such as wood, metal, and concrete.

### 3. Industry Standards

Duct tape shall meet the applicable requirements of the latest revision of the following industry standards:

**UL 723**; Standard for Test for Surface Burning Characteristics of Building Materials

**ASTM E84**; Standard Test Method for Surface Burning Characteristics of Building Materials

#### 4. Requirements

Duct tape shall have the following requirements:

Description	Requirement
Length per roll (yd)	60
Width, nominal (in)	1.89
Thickness, nominal (mils)	10
Adhesive	Rubber
Carrier/backing	Polyethylene (PE) coated cloth, waterproof
Color	Gray or silver
Adhesion, min (oz/in)	51 (to stainless steel test panel)
Tensile strength, min (lb/in)	34
Service/operating temperature range (°F)	40–200

---

#### 5. Packaging

Duct tape shall be packaged to prevent damage during shipping, handling, and storage.

Each standard package shall be legibly marked with the following information:

- Manufacturer identification
- Product description
- SCL stock number
- Quantity

Each shipping container shall be legibly marked with the following information:

- SCL purchase order number
- 

#### 6. Issuance

Stock Unit: RL

---

#### 7. Approved Manufacturers

Stock No.	3M Part No.	Nashua Part No.
736745	6969	357

---

#### 8. Sources

[www.redgreen.com](http://www.redgreen.com)

**Shetab, Muneer**; SCL Standards Engineer, originator, and subject matter expert for 7365.08 (muneer.shetab@seattle.gov)

**Stock Catalog Page, 73-40**, January 11, 2014