

Labeling Tape and Ribbon, Brady Globalmark System



1. Scope

This standard covers the requirements labeling tape and ribbon used with the Brady Globalmark System label maker.

This standard applies to the following Seattle City Light (SCL) stock numbers:

Stock No.	Description
012690	Labeling tape, reflective yellow, 2-1/4" x 50'
012691	Labeling tape, reflective silver, 2-1/4" x 50'
013563	Labeling tape, reflective white, 2-1/4" x 100'
012692	Printing ribbon, black, 4" x 200'

2. Application

Brady Globalmark System labeling tape is used for printing of labels for indoor or outdoor equipment, as well as racks and shelves where high visibility is critical.

The Brady GlobalMark and Brady Labelizer label maker systems, for which SCL stocks labeling tape, are legacy systems no longer being manufactured.

See SCL 7658.30 for labeling tape for the Brady Labelizer.

3. Requirements

Product requirements shall be as defined in Section 6.

Standard Coordinator
Ponet Neuansourinh

Standards Engineering Supervisor
Brett Hanson

Division Director
Bob Risch

4. Packaging

Product shall be packaged to prevent damage during shipping, handling, and storage.

Individual packages shall be legibly marked with:

- Manufacturer name
- Manufacturer catalog number
- Product description
- Seattle City Light stock number





Shipping containers shall be legibly marked with:

- Manufacturer name
- Seattle City Light purchase order number

5. Issuance

Stock Unit: EA

6. Approved Manufacturers

Stock No.	Description	Brady Part No.	
012690	Labeling tape, GlobalMark: <ul style="list-style-type: none"> ▪ Reflective yellow ▪ Cassette ▪ Self-adhesive ▪ 2-1/4" x 50' ▪ Service temperature: 40°F to 158°F ▪ Average outdoor durability: 4–6 years 	B30C-2250-584-YL	
012691	Labeling tape, GlobalMark: <ul style="list-style-type: none"> ▪ Reflective silver ▪ Cassette ▪ Self-adhesive ▪ 2-1/4" x 50' ▪ Service temperature: 40°F to 158°F ▪ Average outdoor durability: 4–6 years 	B30C-2250-584-SL	
013563	Labeling tape, GlobalMark: <ul style="list-style-type: none"> ▪ Reflective white ▪ Cassette ▪ Self-adhesive ▪ 2-1/4" x 100' ▪ Service temperature: 40°F to 158°F ▪ Average outdoor durability: 4–6 years 	B30C-2250-595-WT	
012692	Printing ribbon, GlobalMark: <ul style="list-style-type: none"> ▪ Black ▪ 4" x 200' ▪ Self-contained cartridge ▪ Smear-proof 	B30-R10000	

7. Sources

Neuansourinh, Ponet; SCL Standards Engineer and originator of 7658.40
SCL Stock Catalog page 76-17; May 15, 2014
www.bradyid.com