

**APPLICATION DATA FOR HEAT-SHRINKABLE
 SPLICE COVERS AND CABLE CAPS**

1. Connector and Tubing List

Refer to Guideline U5-1.02/NCB-80 for splicing details.



Splice Cover for Elimination of Taping

Cable Size 600 V Cable		Connectors		Tubing			
AWG / kcmil	OD (in)	Stock No.	OD (in)	Stock No.	ID (in)		Length (in)
					Min. Expanded	Max. Recovered	
Copper							
1/0-4/0	0.530 – 0.690	677359 to 677362	0.510 – 0.690	737450	1.10	0.37	9
250-500	0.770 – 1.010	677363 to 677367	0.750 – 1.060	737452	1.50	0.50	12
Aluminum							
1/0-4/0	0.580 – 0.684	650104	0.906	737450	1.10	0.37	9
350	0.879	650609	1.125				
500	1.114	650611	1.320	737452	1.50	0.50	12
750	1.340	650613	1.590	737455	2.00	0.75	12

2. Cable Limiters

Limiters size 1/0 through 750 kcmil.

Stock No.	ID (in)		Length (in)
	Min. Expanded	Max. Recovered	
737456	3.00	1.25	12

3. Caps for Temporary Insulation of Cable Ends

Stock No.	ID (in)		Approximate Length (in)
	Min. Expanded	Max. Recovered	
737475	0.79	0.36	2.2
737477	1.37	0.70	3.5
737479	2.17	1.00	5.7
737481	4.70	2.76	5.7
737483	3.94	1.77	6.4
737485	2.87	1.26	6.7



STANDARDS COORDINATOR

STANDARDS SUPERVISOR

UNIT DIRECTOR

Robin Byun

Robin Byun

John Shipek

John Shipek

Darnell Cola

Darnell Cola