

## Spray Paint, Gloss



---

### 1. Scope

This standard covers the requirements for gloss spray paint.  
This standard applies to the stock numbers cited in Section 6.

---

### 2. Application

Paint is suitable for use on wood, metal, wrought iron, and paper. Clean up with lacquer thinner.

---

### 3. Requirements

Paint shall be formulated to dry within 15 minutes under normal conditions.  
Paint shall have a gloss finish.  
Net weight/can size shall be 12 oz or 16 oz.  
Cans shall be aerosol-type spray.

---

### 4. Packaging

Paint shall be packaged to prevent damage during shipping, handling, and storage.  
Packages shall be legibly marked with:

- Manufacturer name
- Manufacturer part number
- Product description
- SCL stock number

Shipping containers shall be legibly marked with:





- SCL purchase order number

**5. Issuance**

Stock Unit: CN

---

**6. Approved Manufacturers**

<b>Stock No.</b>	<b>Color</b>		<b>Manufacturer</b>	<b>Catalog No.</b>
724358	Gloss Black		Krylon Industrial	K01501A07
724512	John Deere Yellow		Krylon	1934
724513	Safety Red		Krylon	2116
724514	Glossy White		Krylon Industrial	K01501A07

---

**7. Sources**

**SCL Stock Catalog page 72-21**; April 12, 2018

**Lu, Curtis**; SCL Standards Engineer and originator of 7243.55 (curtis.lu@seattle.gov)

**www.krylon.com**

**www.krylonindustrial.com**