

MATERIAL STANDARD

**TAPE, MASKING
 PRESSURE SENSITIVE**

Scope: This specification covers high performance pressure-sensitive masking tape consisting of a pressure-sensitive adhesive on crepe paper backing.

Applicable Specification: Except as modified by this specification, the tape shall meet the requirements of Federal Specification UU-T-106, Type I, latest revision.

Clean Stripping: When applied to a properly painted surface, this tape shall strip clean, leaving no film or residue and shall not strip off or remove any of the underlying paint coating.

Physical Properties:

- Thickness, maximum 7.5 mils
- Tensile strength, longitudinal pounds per inch of width, minimum 19 lbs.
- Ultimate elongation, minimum 10 per cent
- Adhesion to steel, min. ounces per inch width 30 ounces

Packaging: The tape shall be uniformly and smoothly wound in 60-yard rolls on a suitable core having an inside diameter of $3 \pm 1/32$ inches. The tape shall be packaged with wax paper separators (or equivalent) between rolls.

Reference Specification: Fed. Spec. UU-T-106, Type I, latest revision

Stock Unit: RL

Stock Number	Width, Inches	Packaging Rolls/Case	Approved Manufacturer	
			3M	
			Product No.	Part No. (UPC)
736702	3/4 (18 mm)	48	233+	26334
736704	1 (24 mm)	24	233+	26336
736710	2 (48 mm)	12	233+	26340

ORIGINATOR	STANDARDS COORDINATOR	STANDARDS SUPERVISOR	UNIT DIRECTOR
<i>Jim S. Horn</i>	<i>Charles L. Shaffer</i>	<i>John C. Skinner</i>	<i>Harold Gray</i>